EIN GESCHÄFT OHNE SIGN IST EIN ZEICHEN DAFÜR KEIN GESCHÄFT!

WIE SIE WISSEN, IST LOGO MAT GROSSES IDEAL DAS IMAGE DES UNTERNEHMENS ZU FÖRDERN, KANN SIE KOMBINIEREN
DIE VORTEILE EINER BODENMATTE MIT EINEM AUFFÄLLIGEN DESIGN, DAS BEMÜHUNGEN BRANDING UND MARKETING VERBESSERN KÖNNEN.
SHENZHEN DOTCOM HOUSEWARE PRODUCTS CO., LTD. IST EINER DER PROFESSIONELLEN HERSTELLER UND EXPORTEURE VON LOGO BODEN MIT MEHR ALS ZEHN JAHRE ERFAHRUNGEN IN DIESER LINIE MATTEN. WIR KÖNNEN IHNEN HELFEN, DIE BESTE ART DER LOGOMATTE FINDEN AUF DER GRUNDLAGE DER KOMPLEXITÄT DES DESIGNS UND DER VORGESEHENEN FUNKTION, UNSER LOGO MATTE DECKT EINE BREITE PALETTE VON TYPEN, EINSCHLIESSLICH NYLON-LOGO-MATTE, ACRYL-LOGO-MATTE, POLYESTER LOGO MATTE, WASSER-HOLD-LOGO MATTE 3D-LOGO-MATTE, ETC ...

Product Detail:

A Business with no sign is a sign of No Business!

Pattern#1: Nylon Logo Mat

Dyes are permanently injected deep into the nylon pile so that they will not "rub off"

Twisted nylon pile can absorb water effectively

Rubber backing and borders to help the mats stay in place and prevent curling

Pattern#2: HD Logo Mat

Non-woven surface can absorb water effectively

Ruber border hlelps the wheels move on smoothly

Nitrile rubber backing keep the mat in place



- Combine the benefits of a floor mat with an eye-catching design .
- Enhance brands and market efforts.
- Good water absorption, keep your floor clean and dry.

Our Customers in USA:

NFL

NHL

NBA

Hockey

Apparel

Cosmetics

Boots

Electro

Auto

Foodstuff

Bank

Vacuum

Bicycle

Ski

Soccer

Motorcycle

Preferred Panetone Numbers

Group A

	1	2	3	4	5	6
A	7401C	1205c c7	1215c	7403c	121c	yellow 012c
B	100C	101c	106C	Yellow c	128c	141C
C	102C	803c	113c	115 C	107c	129C
D	108C	3945c	3965C	7404c	116C	109c
E	1225c	135c	142c	136c	130c	143C
F	7406 C	1235C	137c	1375c	131c	1245C

Group B

	1	2	3	4	5	6
A	155C	7506c	726c	162C	148 c	1345c
B	156C	1355c	713c	7509c	157C	715C
C	1495c	151 c	164c	1505c	144C	1385c
D	7510c	7569C 16C	7571c	021C	172c	1655c
E	723c	1595c	471 C	166c	173C	1665c
F	178c	1675c	7524c			

Group C

	1	2	3	4	5	6
A	468c	7611c	728c	4675c	7605c	4725c
B	7501c	467c	873C	118c	1255C	7555c
C	7618c	7525C	4635c	730c	7573c	7593c
D	7591C	7615c	7531c	872C	731c	1615C
E	7567C	4625c	4695c	7603C	1545c	732C
F	7519c	black 4c	7533c	7596C	7631c	504c

Group D

	1	2	3	4	5	6
A	1767c	179C	1788c	1795c	red 032c	485C
B	1797C	199 C	206c	185c	186C	200c
C	1805c	187c	7627	1807C	7426C	warm red c
D	204c	212c	205c	225c	238c	807c
E	232c	227c	208c	207c	201C	202c
F	484c	215c	222c	7645C	7623c	188c

Group E

	1	2	3	4	5	6
A	389 C	382c	359c	373c	802C	368c
B	367c	368c	361c	359c	376c	375c
C	354C	362c	363c	7482c	7732c	370c
D	377c	7745c	7491c	340c	348C	356C
E	349C	7723c	555c	350c	357c	560c
F	5535c	574c	553c	5743c	5815c	419c

Group F

	1	2	3	4	5	6
A	warm gray 1c	427c	Cool Gray 1C	Cool Gray 2C	428c	Cool Gray 3C
B	5315C	537c	Cool Gray 4C	421c	Cool Gray 5C	Cool Gray 6C
C	wram gray 3c	wram gray 4c	Warm Gray 5C	warm grey 6c	Warm Gray 9C	Cool Gray 7C
D	877c	430C	423c	Cool Gray 9C	Cool Gray 10C	424c
E	422c	425c	cool gray 11c	432C	446c	426c
F	7547c	Black 6C	HEXACHROME black c	412C	433c	BLACK

Group G

	1	2	3	4	5	6
A	290c	2707 C	571c	5435c	2905c	310C
B	325c	291U	3115c	2925c	319 C	639c
C	2985c	process blue c	298C	312C	306c	2995C
D	284C	313 C	7461c	3135c	285C	2925c
E	299c	2935c	3005C	300c	307c	7691c
F	7461c	7689c	3015C	2945c	286c	2728 C

Group H

	1	2	3	4	5	6
A	536C	535C	5435c	5415c	7682c	7687C
B	308c	7686c	293C	287C	661c	Reflex Blue C
C	541c	294c	288c	2736c	7694c	2747c
D	281c	654c	289c	2768C	5265c	276c
E	2715C	2726C	272c	2603c	268c	2685c
F	2623C	260c	2593c	261c	2756C	534c

No color limitation, we can do more than above...

Work Flow



Water Absorption Test

SGS

TEST REPORT

No. : SZML131004540
Date : Oct. 16, 2013
Page: 1 of 2

SHENZHEN DOTCOM HOUSEWARE PRODUCTS CO., LTD
RM 927-929, XIANKE MACHINERY-ELECTRICAL BIDG, 4TH BAGUA RD, SHENZHEN, CHINA 518029

The following sample(s) was/ were submitted and identified on behalf of the client as:

Sample Name	:	NYLON PRINTED MAT WITH RUBBER BACKING
SGS Ref No.	:	GZMR131016568
Material	:	NYLON+RUBBER
Spec	:	60×90CM
Manufacturer	:	SHENZHEN DOTCOM HOUSEWARE PRODUCTS CO., LTD
Test Performed	:	Selected test(s) as requested by applicant
Date of Receipt	:	Oct. 11, 2013
Test Period	:	Oct. 11, 2013 to Oct. 15, 2013

Test result(s) : Please refer to the following page(s)

*********To be continued********

Signed for and on behalf of
SGS-CSTC Ltd.

Ramber Li
Authorized Signatory

SZML 058299

Member of the SGS Group (SGS SA)

SGS

TEST REPORT

No. : SZML131004540
Date : Oct. 16, 2013
Page: 2 of 2

Test Information:

Sample description: See photo

Lab environment condition: 23±2℃, 50±5%RH

No.	Test item	Test method	Test condition	Test result
1	Water absorption	ASTM C1016-02 (2008)[1] Procedure A	Specimen:300×50×4.6mm Immersion condition: 23±2℃, 24h	0.695g/cm[3] (See note 1)

Note: 1. Water absorption, g/cm[3] = (Final mass- initial mass) / Initial dry volume.
2. All test specimens were cut from the sample.
3. The above test was carried out by a SGS laboratory.

Photo:

*********End of report*********

SZML 058300

Member of the SGS Group (SGS SA)

Color Fastness & Flammability Test

Intertek

Test Report

Number: GZHT00870233

Tests Conducted (As Requested By The Applicant)

1 Color Fastness To Washing (AATCC 61-2010, Test No. 2A, 45 Minutes Mechanical Wash At 120ºF In 0.15% AATCC WOB Detergent Solution With 50 Steel Balls):

Color Change	4
Color Staining	
-Acetate	4.5
-Cotton	4
-Nylon	4.5
-Polyester	4.5
-Acrylic	4.5
-Wool	4.5

2 Color Fastness To Crocking (AATCC 8-2007):

Dry	4.5
Wet	4.5

3 Color Fastness To Light (AATCC 16-2004, Option 3, Xenon-Arc Lamp):

20 Hours Exposure	
Grade	4

SP / hpwjxu

Page 3 Of 4

Intertek Testing Services (Guangzhou) Ltd.
3/F, Hengyun Building, 235 Kaifa Ave., Guangzhou
Economic & Technological Development District,Guangzhou,China
天祥（广州）技术服务有限公司
中国广州经济技术开发区开发大道 235 号恒运大厦 3 楼
Tel: (8620)8396 6868 Fax: (8620)8222 8169 PostCode:510730

Intertek

Test Report

Number: GZHT00870233

Tests Conducted (As Requested By The Applicant)

4 Flammability Test For Carpets And Rugs (US CPSC 16 CFR Part 1631):

The Apparatus And Methods Of Testing Were Those Described In 16 CFR Part 1631 Standard For The Surface Flammability Of Small Carpets And Rugs (FF2-70).

Requirement
(1) Test Criterion:
The Charred Portion Does Not Extend To Within One Inch Of The Edge Of The Hole In The Flattening Frame At Any Point.
(2) Acceptance Criterion:
At Least 7 Of The 8 Specimens Must Meet The Test Criterion For The Material To Be Classified As Resistance To Flammability.

Test Result :

The Nearest Distance From Burnt Area To The Frame Edge

Original (in)	
3.7	3.5
3.6	3.7
3.6	3.8
3.8	3.7

Interpretation Of Test Result :

Number Of Specimens Meet The Test Criterion	8

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.

SP / hpwjxu

Page 4 Of 4

Intertek Testing Services (Guangzhou) Ltd.
3/F, Hengyun Building, 235 Kaifa Ave., Guangzhou
Economic & Technological Development District,Guangzhou,China
天祥（广州）技术服务有限公司
中国广州经济技术开发区开发大道 235 号恒运大厦 3 楼
Tel: (8620)8396 6868 Fax: (8620)8222 8169 PostCode:510730

Buyers' Guide

Buyers Guidelines

1.Color Difference

Due to process of printing onto a fiber surface and the limitation of print machine, the PMS colors and design can only be matched as close as possible.

2.Tolerance



Size tolerance is +/-3%.
Quantity tolerance is +/-5%.
Weight tolerance is +/-5%.

3. Service

Online service, solving your problem in 24 hours

4.Cleaning Recommendation

Shake mat ourside for loose soill; Vacuum cleaner at slow speed with brush will be good to take the deep dry soil.

Eigenschaften:

1) ziehen die Aufmerksamkeit der Menschen, große Ideal für die Werbung.
2) Sublimationsdruck, die Begrenzung ist Ihr Image.
3) Leicht zu reinigen, maschinenwaschbar.
4) Hohe Verkehrsbereich, Innen- und Außenanwendungen.

5) 7 Tage Produktionszeit.
6) Kein MOQ Anforderung, können Sie nur 1pc bestellen.

Ideal Nutzung:

1) Einzelhandelsgeschäft
2) Point-of-Purchase-Anzeige
3) Messe
4) Produktförderung
5) Autohäusern

Standardgröße:

40x60cm, 60x90cm, 83x120cm, 103x150cm, etc ...