



Test Report

Number: GZHT00870233

Applicant: SHENZHEN DOTCOM HOUSEWARE PRODUCTS CO., LTD.
RM 827,XIANKE MACHINERY-ELECTRICAL
BLDG,BAGUA 4TH RD,SHENZHEN,CHINA 518029
深圳市德康家居用品有限公司
深圳市福田区八卦四路先科机电大厦 827 室
Attn: SHIRLEY ZHAO

Date: Oct 06, 2012

Sample Description As Declared :

No. Of Sample : One
Fibre Content : Nylon
Material : Nylon Printed Mat
Finishing : Without Flam Retardant
End Uses : Spread On The Floor
Season : -
Colour : Print
Style No. : -
Order No./PO No. : -
Buyer's Name : -
Manufacturer's Name : Shenzhen Dotcom Houseware Products Co., Ltd.
Ref. : Vendor: Shenzhen Dotcom Houseware Products Co., Ltd.

Applicant's Provided Care Instruction/Label : -

Date Received : Sep 24, 2012
Date Test Started/Final Information Confirmed : Sep 24, 2012

Prepared And Checked By:
For Intertek Testing Services
Textile And Footwear Division

Lin Lin
Assistant General Manager



SP / hpwjxu



Test Report

Number: GZHT00870233

Conclusion:

Color Fastness To Washing	M
Color Fastness To Crocking	M
Color Fastness To Light	#
Flammability Test	M1

Note : M = Commercially Acceptable
= No Comment
C = Conform Label
- = Did Not Perform

F = Fail
N/A = Not Applicable
* = See Remark

Remark:

M1 Based upon the results of the flammability test reported, the sample submitted for testing meets the performance requirements of 16 CFR part 1631 (FF2-70).

Prepared And Checked By:
For Intertek Testing Services
Textile And Footwear Division

Lin Lin
Assistant General Manager

SP / hpwjxu



Page 2 Of 4



Test Report

Number: GZHT00870233

Tests Conducted (As Requested By The Applicant)

1 Color Fastness To Washing (AATCC 61-2010, Test No. 2A, 45 Minutes Mechanical Wash At 120°F In 0.15% AATCC WOB Detergent Solution With 50 Steel Balls):

Color Change	4
Color Staining	
-Acetate	4.5
-Cotton	4
-Nylon	4.5
-Polyester	4.5
-Acrylic	4.5
-Wool	4.5

2 Color Fastness To Crocking (AATCC 8-2007):

Dry	4.5
Wet	4.5

3 Color Fastness To Light (AATCC 16-2004, Option 3, Xenon-Arc Lamp):

<u>20 Hours Exposure</u>	
Grade	4

SP / hpwjxu



Test Report

Number: GZHT00870233

Tests Conducted (As Requested By The Applicant)

4 Flammability Test For Carpets And Rugs (US CPSC 16 CFR Part 1631):

The Apparatus And Methods Of Testing Were Those Described In 16 CFR Part 1631 Standard For The Surface Flammability Of Small Carpets And Rugs (FF2-70).

Requirement

- (1) Test Criterion:
The Charred Portion Does Not Extend To Within One Inch Of The Edge Of The Hole In The Flattening Frame At Any Point.
- (2) Acceptance Criterion:
At Least 7 Of The 8 Specimens Must Meet The Test Criterion For The Material To Be Classified As Resistance To Flammability.

Test Result :

The Nearest Distance From Burnt Area To The Frame Edge

<u>Original</u>	
(in)	
3.7	3.5
3.6	3.7
3.6	3.8
3.8	3.7

Interpretation Of Test Result :

Number Of Specimens	
Meet The Test Criterion	8

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.

SP / hpwjxu