

Why Choose Us?



Factory

We've passed BSCI's audits and we are committed to the benefits of society.



Certificate

Oeko-Tex Standard 100, ISO9001, ISO14001 certified, all of our mats are eco-friendly.



Quality

**The 1st Chromojet dye-injection
carpet printing factory in China**



Assurance

Alibaba Trade Assurance
to make sure on-time ship
& quality safeguard.

NO SIGN□□□□□□□□**NO**□□□□□□□□

[illegible][illegible][illegible][illegible]

3D-...

Product Detail:

A Business with no sign is a sign of No Business!

Pattern#1: Nylon Logo Mat

Dyes are permanently injected deep into the nylon pile so that they will not "rub off"



Twisted nylon pile can absorb water effectively

Rubber backing and borders to help the mats stay in place and prevent curling

Pattern#2: HD Logo Mat

Non-woven surface can absorb water effectively



Ruber border hhelps the wheels move on smoothly

Nitrile rubber backing keep the mat in place

- Combine the benefits of a floor mat with an eye-catching design .
- Enhance brands and market efforts.
- Good water absorption, keep your floor clean and dry.



Pile Options:

DETAILS

1

Item#: DK-2450
Pile Weight: 450g/sqm
Pile Height: 3mm



2

Item#: DK-2000
Pile Weight: 600g/sqm
Pile Height: 4mm



3

Item#: DK-2200
Pile Weight: 700g/sqm
Pile Height: 5mm



4

Item#: DK-2300
Pile Weight: 950g/sqm
Pile Height: 7mm



Back Options:

DETAILS


1

Normal Rubber
Weight: 2,000g/sqm



2

Nitrile Rubber
With cleat
Weight: 1,800g/sqm



3

TPR
Weight: 900g/sqm



Our Customers in USA:



NFL



NHL



NBA



Hockey



Apparel



Cosmetics



Boots



Electro



Auto



Foodstuff



Bank



Vacuum



Bicycle



Ski



Soccer



Motorcycle

Preferred Panetone Numbers

	1	2	3	4	5	6		1	2	3	4	5	6
A	7401C	1205c cf	1215c	7403c	121c	yellow 012c	A	155C	7506c	726c	162C	148c	1345c
B	100c	101c	106c	Yellow c	128c	141c	B	156C	1355c	713c	7509c	157C	715C
C	102c	803c	113c	115 C	107c	129c	C	1495c	151 c	164c	1505c	144C	1385c
D	108c	3945c	3965c	7404c	116C	109c	D	7510c	7569C 16C	7571c	021C	172c	1655c
E	1225c	135c	142c	136c	130c	143C	E	723c	1595c	471 C	166c	173C	1665c
F	7406 C	1235C	137c	1375c	131c	1245C	F	178c	1675c	7524c			



	1	2	3	4	5	6		1	2	3	4	5	6
A	468c	7611c	728c	4675c	7605c	4725c	A	1767c	179c	1788c	1795c	red 032c	4650
B	7501c	467c	873C	118c	1255C	7555c	B	1797C	199 C	206c	185c	168C	200c
C	7618c	7525C	4635c	730c	7573c	7593c	C	1805c	187c	7627	1807C	7426C	warm red c
D	7581C	7615c	7531c	872C	731c	1615C	D	204c	212c	205c	225c	238c	807c
E	7567C	4625c	4665c	7603C	1545c	732C	E	232c	227c	208c	207c	201C	202c
F	7519c	black 4c	7533c	7596C	7631c	504c	F	484c	215c	222c	7645C	7623c	188c

	1	2	3	4	5	6		1	2	3	4	5	6
A	389 C	382c	359c	373c	802C	368c	A	warm gray 1c	427c	Cool Gray 1C	Cool Gray 2C	428c	Cool Gray 3C
B	367c	368c	361c	359c	376c	375c	B	5315C	537c	Cool Gray 4C	421c	Cool Gray 5C	Cool Gray 6C
C	354C	362c	363c	7482c	7732c	370c	C	warm gray 3c	warm gray 4c	Warm Gray 5C	warm gray 6c	Warm Gray 9C	Cool Gray 7C
D	377c	7745c	7491c	340c	348C	356C	D	877c	430C	423c	Cool Gray 9C	Cool Gray 10C	424c
E	349C	7723c	555c	350c	357c	560c	E	422c	425c	cool gray 11c	432C	446c	426c
F	5535c	574c	593c	5743c	5815c	419c	F	7547c	Black 6C	HEXACHROME black c	412C	433c	BLACK

	1	2	3	4	5	6		1	2	3	4	5	6
A	290c	2707 C	571c	5435c	2905c	310C	A	536C	535C	5435c	5415c	7682c	7687C
B	325c	291V	3115c	2825c	319 C	639c	B	308c	7696c	293C	287C	981c	Reflex Blue C
C	2865c	process blue c	298C	312C	306c	2995C	C	541c	294c	286c	2756c	7694c	2747c
D	284C	313 C	7461c	3135c	285C	2925c	D	281c	654c	289c	2768C	5265c	276c
E	299c	2935c	3005C	300c	307c	7681c	E	2715C	2725C	272c	2603c	268c	2665c
F	7461c	7689c	3015C	2945c	286c	2728 C	F	2623C	260c	2593c	261c	2756C	534c

No color limitation, we can do more than above...

Work Flow



Water Absorption Test



No. : SZML131004540
Date : Oct. 16, 2013
Page: 1 of 2

SHENZHEN DOTCOM HOUSEWARE PRODUCTS CO., LTD
RM 927-929, XIANKE MACHINERY-ELECTRICAL BLDG. 4TH BAGUA RD. SHENZHEN, CHINA 518029

The following sample(s) was/ were submitted and identified on behalf of the client as

Sample Name	NYLON PRINTED MAT WITH RUBBER BACKING
SGS Ref No.	GZMR131016568
Material	NYLON+RUBBER
Spec	60 x 90CM
Manufacturer	SHENZHEN DOTCOM HOUSEWARE PRODUCTS CO., LTD
Test Performed	Selected test(s) as requested by applicant
Date of Receipt	Oct. 11, 2013
Test Period	Oct. 11, 2013 to Oct. 15, 2013

Test result(s): ☐ Please refer to the following page(s):
*****To be continued*****

Signed for and on behalf of
SGS-CSTC Ltd.



Ramber Li
Authorized Signatory

[illegible]

No. : SZML131004540
Date : Oct. 16, 2013
Page: 2 of 2

Test information:
Sample description: See photo
Lab environment condition: 23±2°C, 50±5%RH

No.	Test item	Test method	Test condition	Test result
1	Water absorption	ASTM C1016-02 (2008) ¹⁾ Procedure A	Specimen 300×50×4.6mm immersion condition: 23±2℃, 24h	0.665g/cm ³ (See note 1)

Note: 1. Water absorption, $\text{g/cm}^3 = (\text{Final mass} - \text{initial mass}) / \text{initial dry volume}$
 2. All test specimens were cut from the sample.
 3. The above test was carried out by a SGS laboratory.

Photo:

Photo:



*****End of report

[illegible][illegible]

4

57
6MOQ1

-
- 1
- 2
- 3
- 4
- 5

40x60cm60x90cm83x120cm103x150cm...